

# Fire-Resistant Mineral Core 45-60 Min / Bonded Construction

Commercial Series – Molded Panel Doors  
Cendura™ by Masonite Architectural™

	PRODUCT SPECIFICATIONS	INTERIOR USE ONLY			
<b>DIMENSIONS</b>	<b>Thickness</b>	1-3/4"			
	<b>Maximum Size</b>	ITS-WH AND UL			
			45-60 Min Fire-rated Neutral Pressure	45-60 Min Fire-rated Cat B Positive Pressure	
		Singles	3'0" x 7'0"	3'0" x 7'0"	
Pairs	6'0" x 7'0"	6'0" x 7'0"			
	<b>Prefit Size (Default)</b>	Singles: beveled 2 edges, 7/32" width and 3/4" height Pairs: beveled 2 edges, 3/16" width and 3/4" height			
<b>CONSTRUCTION</b>	<b>Surface Material</b>	Molded Panel (2-panel square top smooth designs only)			
	<b>Crossbands</b>	N/A			
	<b>Vertical Edges</b>	Hardwood Composite Fire Stile			
	<b>Horizontal Edges</b>	Manufacturer's standard construction per label service listing			
	<b>Face &amp; Core Assembly Adhesive</b>	Type 1			
	<b>Core Construction</b>	Mineral Core			
	<b>Lite Openings / Louvers</b>	N/A			
	<b>Distance from Lock &amp; Lite Cutouts</b>	N/A			
	<b>Details</b>	N/A			
	<b>Machining</b>	Machining preparation per hardware manufacturer's templates Some limitations apply			
	<b>Factory Finish</b>	Prime, standard and custom paint colors			
<b>CREDITS &amp; STANDARDS</b>	<b>Environmental Standards</b>	CARB PH2			
	<b>Quality Standards</b>	WDMA I.S.1A Architectural Wood Flush Doors (Standard Construction)			
	<b>WDMA Performance Duty Level</b>	N/A			
<b>WT.</b>	<b>Door Weight</b>	Average: 3.7 lbs/sf			
	<b>Warranty</b>	Limited Lifetime. No exterior warranty. Interior use only.			