

Particleboard Core Non-Rated & 20 Min / Non-Bonded Construction

Commercial Series – Molded Panel Doors
Cendura™ by Masonite Architectural™

	PRODUCT SPECIFICATIONS	INTERIOR USE ONLY			
DIMENSIONS	Thickness	1-3/4"			
	Maximum Size	ITS-WH AND UL			
			Non-Rated	20-Min Fire-rated Neutral Pressure	20-Min Fire-rated Cat B Positive Pressure
		Singles	3'0" x 7'0"	3'0" x 7'0"	3'0" x 7'0"
Pairs	6'0" x 7'0"	6'0" x 7'0"	6'0" x 7'0"		
	Prefit Size (Default)	Singles: beveled 2 edges, 7/32" width and 7/8" height Pairs: beveled 2 edges, 3/16" width and 7/8" height			
CONSTRUCTION	Surface Material	Molded Panel (6-panel or 2-panel square top smooth designs)			
	Crossbands	N/A			
	Vertical Edges	Finger Joint Softwood (1-1/4" before trim)			
	Horizontal Edges	Mill Option: Structural Composite Lumber or Softwood (1-1/4" before trim)			
	Face & Core Assembly Adhesive	Type 1			
	Core Construction	Wood-based Particleboard Core			
	Lite Openings / Louvers	N/A			
	Distance from Lock & Lite Cutouts	N/A			
	Details	N/A			
	Machining	Machining preparation per hardware manufacturer's templates			
	Factory Finish	Prime, standard and custom paint colors			
CREDITS & STANDARDS	Environmental Standards	CARB PH2			
	Quality Standards	WDMA I.S.1A Architectural Wood Flush Doors (Standard Construction)			
	WDMA Performance Duty Level	N/A			
WT.	Door Weight	Average: 5.5 lbs/sf			
	Warranty	Limited Lifetime. No exterior warranty. Interior use only.			